



LMB-120

铝门窗单头组角机 Corner Crimping Machine for Aluminum Window and Door

[性能特点]

- 动力由液压系统控制，工作平稳可靠。
- 左右冲头刚性同步进给，避免组角过程的无益变形，使窗角连接更牢。
- 同步进给机构调整便捷。
- 可配置双刃组角刀，使隔热断桥铝门窗组角强度更高。

[Product Features]

- The frame is specially jointed by steel with high quality and then does special process.
- Adopt new mechanical linkage device, realized complete synchronous corner combining.
- Synchro Feeding structure make the adjustment very easy.
- Screw thread regulates the distance between up and down crimping blade ensures regulates blades easily.
- It is collocate single cutter of many points crimping cutter ensure reliably crimping heat insulation aluminum windows and doors.

技术参数 Technical Parameters

电 源	Power supply	380V 50Hz
电机功率	Motor power	1.5kW
额定油泵压力	Rated oil pump pressure	16Mpa
电机转速	Motor rotational speed	1400r/min
适用型材宽度	Profile processing width	90mm
气源工作压力	Total combining pressure	0.5-0.8Mpa
总组角压力	General pressure of corner combining	48kN
外形尺寸	Contour dimension	1850 × 1680 × 1210mm
重量	Weight	300kg

